SCRR492



Product Features:

Complete stainless steel construction Interior and exterior are entirely constructed from stainless steel for lasting durability and easy cleanup Forced air cooling Top-mounted commercial fan ensures rapid temperature recovery Automatic defrost with adjustable cycle Adjustable cycle defrost operation ensures the unit avoid temperature spikes and ice buildup defrost Self-closing doors Closes to save energy but will remain open when the door is opened at a 90° angle for easier loading Alarm will beep 3 times if the door is left open for 30 seconds, 5 times at 60 seconds, and will Open door alarm sound continuously if the door is open for more than 5 minutes Temperature alarm Visual and audible alarms alert if the interior temperature rises or falls out of set range Commercial grade casters Ships with a set of casters (2 locking) for easy mobility as needed Microprocessor control panel Digital controls with a large LED readout in Celsius or Fahrenheit for intuitive temperature management Min/max display Control panel provides a readout of the low and high temperatures in 15 minute increments

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

83.75" x 55.25" x 31" (H x W x D)

49 cu.ft. commercial reach-in refrigerator in complete stainless steel

Highlights:

Commercially listed to NSF standards

Stainless steel interior and exterior cabinet for true durability in high traffic commercial settings

Optimized forced air cooling for excellent temperature stability and uniformity with rapid recovery after door openings and product loading



SCRR492 Specifications:

Overview	
Nominal Height	84.0" (213 cm)
Height of Cabinet	83.75" (213 cm)
Nominal Width	56.0" (142 cm)
Width	55.25" (140 cm)
Nominal Depth	31.0" (79 cm)
Depth	31.0" (79 cm)
Depth with Handle	31.0" (79 cm)
Depth with door at 90°	56.5" (144 cm)
Capacity	49.0 cu.ft. (1388 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	Stainless Steel
US Electrical Safety	UL
Canadian Electrical Safety	ULC
Sanitation	ETL-S
Amps	7.5
Voltage/Frequency	115 V AC/60 Hz
Weight	441.0 lbs. (200 kg)
Parts & Labor Warranty	2 Years
Compressor Warranty	5 Years
UPC	761101062365
Refrigerator Features	
Door Swing	French
Shelf Type	Wire
Shelf Qty	8
Adjustable Shelves	Yes
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R290
Refrigerant Amount	3.2oz.
High Side PSI	290.0
Low Side PSI	155.0
Wheel Qty	4
Interior Light	Yes
Temperature Range	33 to 41ºF
Dimensions	
Interior Height	51.5" (131 cm)

Interior Width	50.5" (128 cm)
Interior Depth	27.0" (69 cm)



